

CARATTERISTICHE TECNICHE PRINCIPALI

- Diffusore: Ø 15 - 16 - 17 - 17,5 - 18 - 19 - 19,5 - 20 - 21
- Per motori 2-4 tempi
- Valvola gas cilindrica
- Dispositivo avviamento a circuito indipendente
- Sistema del minimo con getto e vite regolazione miscela
- Sistema del massimo con regolazione meccanica della miscela a mezzo spillo conico
- Attacco a manicotto con riduzione isolante da Ø 26 a Ø 24 - 23 per i tipi PHBG A-C
attacco per montaggio elastico da Ø 25 per i tipi PHBG B e D
- Attacco presa aria Ø 32 o Ø M32 x 1,25 per montaggio cornetti e raccordi

MAIN TECHNICAL FEATURES

- Choke: Ø 15 - 16 - 17 - 17,5 - 18 - 19 - 19,5 - 20 - 21
- 2-4 stroke
- Piston-type throttle valve
- Independent starting circuit
- Idling system with jet and mixture adjusting screw
- Main circuit with mechanical mixture adjustment by means of a conical needle
- Connection by insulating reducing socket from Ø 26 to Ø 24-23 for PHBG A-C types and Ø 25 elastic fitting connection for PHBG B and D types
- Air inlet connection Ø 32 and Ø M32 x 1.25 for trumpet or union assembly

